



CONNECTION DIAGRAM

1	13	PO163-17.625	COVER
1	12	PO163-8.812	COVER

2	11	PO-163-2.937	COVER
1	10	CU-113	CLAMP
	9	MWC 14 (9) U0	CABLE, INSULATED
	8	MWC 14 (9) U9	CABLE, INSULATED
	7	PO-162	END FITTING, CABLE ENTRY
	6	SCBR0540 BNS	BINDER HEAD SCREW
	5	TE-112-2	LUG, TERMINAL
	4	PO-161	END FITTING, BLANK
	3	JJ-170	RECEPTACLE TWIST LOCK AG.
	1	CA-588-1	CABLE, RUBBER SHIELDED
	1	MS-1891	AC STRIP

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
		THE TECHNICAL MATERIEL CORP.	
		MAMARONECK, NEW YORK	
		AX-157 ASS'Y	
		A.C. POWER STRIP	
		CHECKED	FINAL APPROVAL
		DRAWN	A1772
		DATE	ENG. APP.
		CHECKER	
		DRAFTS	
		DATE	
		CH. NO.	
		17643	
		1-9-67	
		RME	

ITEM (6) REPLACES DISCARDED SCREW

TOLERANCES  
 DEC. DIM. ±  
 FRAC. DIM. ±  
 ANGULAR DIM. ±

SCALE:  
 MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES