REVISIONS						
ZONE	SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD	APPD
—	A	SEE SHEET 2 of 2 REVISION "A"	2-21-63	8327			
D-11	B	(1) "F" & (5) "J" HOLES ADDED, (1)"C" HOLE DELETED	2-27-63	8403			
—	C	AS SHEET 1 OF (3) SHEETS, WAS B REVISED PER CLARIFIED DWG	4/15/63	11220			
—	D	UPDATED & CLARIFIED DWG	10/15/63	11587			
D-11 D-5,E-5	E	ON HOLE SCHED. ADDED (4) L- HOLES 5/16 DIA. "C" QUAN. WAS 3 CHANG. (2) "C" HOLES TO "L", RELOC. (1) UNMARKED HOLE	3.18.64	11054	ASB		
B-11 F-8,8D-1	F	ON HOLE SCHED. "B" HOLES WAS 51, "F" HOLES WAS 8 4 "B" HOLE CALLOUTS ADDED	4.23.64	11277	ASB		
—	G	SEE SHEET 3 OF 3 FOR REVISION "G"	6.16.64	11588	ASB		
~	H	4 "C"-HOLES CHNG. TO "D"-HOLES, 1 "E"-HOLE ADDED	7.24.64	11738	ASB		

HOLE SCHEDULE		
LETTER	SIZE	NO. REQD
UNMARKED	DR #53 (.059)	AR *
B	DR #42 (.093)	54
C	1/8 DIA	3
D	5/32 "	15
E	1/4 "	17
F	DR. #27 (.144)	7 *
G	DR #38 (.101)	53 *
H	19/64 "	2
J	DR #51 (.067)	5
L	5/16 DIA.	2

* SEE NOTE 3



PRINTED CIRCUITRY
CAUTION: THIS SIDE UP WHEN PRINTED

SCALE: APPROX.
REDUCE TO FINAL DIMENSIONS AS SHOWN BOTH FRONT & REAR VIEWS. (FRONT VIEW ON SHEET #2)

NOTES:
1. MAT'L: SYNTHANE G-11 EPOXY GLASS LAMINATE 3/32 THK, .002 COPPER CLAD (2) SIDES.
2. DO NOT PRINT LETTER DESIGNATIONS AS SHOWN ON BOARD.
3. HOLES ARE TO BE "PLATED-THRU" WITH MINIMUM COPPER PLATING THICKNESS OF .0015 ± MIN. SOLDER-PLATE (TIN) THICKNESS OF .0005.
   MIN. FINISHED DIA OF "PLATED-THRU HOLES:
   UNMARKED ~ .050
   F ~ .136
   G ~ .093
4. ETCHED CIRCUIT TO BE TINNED .0005 THK.
5. SEE PURCHASING NOTE.

PURCHASING NOTE:
ORIGINAL ARTWORK TO BE SUPPLIED TO VENDOR FOR MANUFACTURING. ARTWORK MUST BE RETURNED TO TMC IN GOOD CONDITION AS SOON AS POSSIBLE

H A-2509

DO NOT FOLD ORIGINAL

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
STRUMER			LIST OF MATERIAL	

MATERIAL: SEE NOTE 1		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
FINISH: —		TITLE: PRINTED CIRCUIT BD. ASSY (BOTTOM VIEW SHOWN)	
1 QTY/UNIT	GPR-92 MODEL USED ON	A2509 SHEET 2 ASSY. NO.	
SCALE 2:1 APPROX.	CODE	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	DRAWN W.S. 11-7-62 / CHECKED 11-14-63 / ELECT. DES. 10-25-63 / MECH. DES. 11-11-63
		DECIMALS .X ± .05, .XX ± .01, .XXX ± .005 — FRACTIONS ± 1/64 — ANGLES ± 0° 30' — TOLERANCES	FINAL APPROVAL / DATE
		THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.	A-2509 H — SHEET 1 OF 3 — REV. LTR.

NOTES

TMC FORM 111