

SYMBOL(S)	ITEM NO.	USED TO MOUNT	QTY	USED ON		DATE
				MODEL	ASSY. NO.	
		HFA-1				10/1/64
						A2853

REQ. PER UNIT	ITEM	DESCRIPTION	PART NO.	REQ. ITEM	DESCRIPTION	SYMBOL
1						
2	C7039,7083	WIRING		1	TE169-1	TERMINAL, FEEDTHRU
3	TE149			1	TE149-120	TERMINAL, LUG, NO. 4
4	CE103			1	SCBP0632BN5	SCREW, MACHINE
6	TE149			1	SCBP0440BN4	SCREW, MACHINE
7	CE103			1	PX140-8-034	INSULATION SLEEVING, SZ 20
8	C7039,7083	WIRING		2	PX104-3-034	INSULATION SLEEVING, SZ 20
9	C7039	WIRING		1	PX104-1-034	INSULATION SLEEVING, SZ 20
10	C7083	WIRING		1	NTH0632BN8	NUT, PLAIN, HEX
11	TE149			1	NTH0440BN6	NUT, PLAIN, HEX
12	CE103			1	MS3443	SHIELD, RF, CHANNEL B
13	R7111 WIRING			1	LWE06MRN	WASHER, LOCK, EXTERNAL
				1	LWE04MRN	WASHER, LOCK, EXTERNAL
				2	CE103-5	CAPACITOR, FIXED, ELECTROLYTIC
				1	BS100	SOLDER, TIN ALLOY

LAWNSBY		DESCRIPTION		SYMBOL	
THE TECHNICAL MATERIEL CORP.		MAMARONECK, NEW YORK			
SHIELD/CAPACITOR ASSEMBLY, CHANNEL B					
JS 10-2-69	ENG COORD	10-2-69	CHECKED	FINAL APPROVAL	
TYPE & TEMPER		HEAT TREAT. SPEC.		ELEC. DES. APP. MECH. DES. APP.	
MATERIAL		FINISH & SPEC. NO.		A2853	
DATE		10-7-64	CHECKER	A2853	
SCALE		92.	CH. NO.		
DESCRIPTION		ORIGINAL RELEASE FOR PRODUCTION			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		TOLERANCES			
DECIMALS		FRACTIONS			
.X ± .05		± 1/64			
.XX ± .01		ANGLES			
.XXX ± .005		± 0° 30'			