



ELECTRICAL SPECIFICATIONS:

COIL Latch Relay - 1100 ohm \pm 10%
 Unlatch Relay - 0.93 ohm \pm 10%
 Both Coils moisture resistant varnished.

PILE UP 4 Form C (4 P.D.T.) (Latch Relay)

CONTACTS Code 15 1/4 silver cadium rated 25 amps
 125 V AC resistive.

ADJUSTMENT Latch - Operate - 220 V 60 cycle AC or
 less. Unlatch - Operate - 1 ampere.
 Non - Operate - .980 amperes

MOUNTING DATA:

Four 5/32" diameter holes on 1-1/2" X 1-1/4" mounting centers.

NOTE

NOTE:

PHYSICAL APPEARANCE OF RELAYS
 WILL VARY DEPENDING OF VENDOR'S
 CONFIGURATION. IN ALL CASE'S ASSY.
 WILL BE ELECTRICAL & MECHANICAL
 INTERCHANGEABLE

NOTICE TO PERSONS RECEIVING THIS DRAWING

THE TECHNICAL MATERIEL CORPORATION claims
 proprietary right in the material disclosed hereon.
 This drawing is issued in confidence for engineering
 information only and may not be reproduced or used
 to manufacture anything shown hereon without per-
 mission from THE TECHNICAL MATERIEL CORPORA-
 TION to the user. This drawing is loaned for mutual
 assistance and is subject to recall at any time.

Property of:

THE TECHNICAL MATERIEL CORPORATION
 MAMARONECK, NEW YORK

ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
B		NOTE ADD	10-31-85	22115	GDL		Q2
A	1	CLERICAL CHANGE	9.2.64	-	WB	@	

TOLERANCES SCALE:

DEC. DIM. \pm
 FRAC. DIM. \pm
 ANGULAR DIM. \pm

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

1	GPT-10K	AR-161	A-1667	8-17-64
REQ. PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
USED ON				

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
STOCK SIZE			
		P.A. PLATE OVL D RELAY ASS'Y.	
MATERIAL			
TYPE & TEMPER	HEAT TREAT. SPEC.	DRAWN	CHECKED
FINISH & SPEC. NO.		ELEC. DES. APP.	MECH. DES. APP.
		AR-100	B