



ELECTRICAL SPECIFICATIONS:

COIL 11,000 ohm  $\pm$  10%  
 PILE UP 4 Form C (4 P.D.T.)  
 CONTACTS  $\frac{3}{16}$ " silver cad oxite  
 Rated 10 A. 125 VAC Resistive  
 ADJUSTMENT Operate .010 amperes -  
 Non operate .009 amperes

MOUNTING DATA:

Four  $\frac{9}{64}$ " diameter holes on  $\frac{7}{8}$ " X  $\frac{3}{8}$ " mounting centers.

NOTE: ORIGINAL RELAY IS NO LONGER AVAILABLE, CURRENT RELAY IS ELECTRICALLY AND MECHANICALLY INTERCHANGEABLE. DIMENSIONS ARE FOR REFERENCE ONLY.

*OK*

ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
B		CHG. DIM. ADD NOTE	9-12-75	21289		<i>WB</i>	<i>WB</i>
A	1	CLERICAL CHANGE	9.2.64	-		<i>WB</i>	<i>@</i>

  

TOLERANCES		SCALE:	
DEC. DIM. $\pm$	MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES		
FRAC. DIM. $\pm$			
ANGULAR DIM. $\pm$			

1	GPT-10K	AR-161	A-1704	8-18-64
REQ. PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
USED ON				

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
STOCK SIZE		PA BIAS RELAY ASS'Y.	
MATERIAL			
TYPE & TEMPER	HEAT TREAT. SPEC.	DRAWN <i>WB</i>	CHECKED <i>WB</i>
FINISH & SPEC. NO.		FINAL APPROVAL <i>WB</i>	
		ELEC. DES. APP.	MECH. DES. APP.
		AR-105 B	