



ELECTRICAL SPECIFICATIONS:

COIL 11,000 ohm ± 10%
 PILE UP 4 Form C (4 P.D.T.)
 CONTACTS 3/16" silver cad oxite
 Rated 10 A. 125 VAC Resistive
 ADJUSTMENT Operate .010 Amperes
 Non - operate .009 Amperes

MOUNTING DATA:

Four 9/64" diameter holes on 7/8" X 3/8" mounting centers.

NOTE: ORIGINAL RELAY IS NO LONGER AVAILABLE. CURRENT RELAY IS ELECTRICALLY AND MECHANICALLY INTERCHANGEABLE. DIMENSIONS ARE FOR REFERENCE ONLY.

ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
B		CHG DIM, ADD NOTE	9-12-75	21289	988	988	
A	1	CLERICAL CHANGE	9.2.64	+	LB	@	
TOLERANCES		SCALE:					
DEC. DIM. ±		MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS					

1	GPT-10K	AR-161	A-1705	8-24-64
REQ.	MODEL	PROJECT NO.	ASS'Y. NO.	DATE

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
		STOCK SIZE	
		IPA BIAS RELAY ASS'Y.	
		MATERIAL	
		TYPE & TEMPER	HEAT TREAT. SPEC.
		DRAWN	CHECKED
			FINAL APPROVAL
			AR-106 B