



Contact Arrangement - 4 Pole, Double Throw  
 Coils - 115 VAC, 44 Amp.  
 Contacts - Fine Silver, 5 A. at 115 VAC

ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
B		SCHEMATIC REVISED	7-10-75	21239	GDL	<i>[Signature]</i>	<i>[Signature]</i>
A	1	Wire Colors chgd.	10/16/59	143B	16	<i>[Signature]</i>	<i>[Signature]</i>
TOLERANCES			SCALE:		NPL 2A1782		
DEC. DIM. ±			MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.				
FRAC. DIM. ±			REMOVE ALL BURRS AND SHARP EDGES				
ANGULAR DIM. ±							

1	MCLU-2	ATG-2	10/12/59
REQ. PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.
USED ON			

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
STOCK SIZE		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
MATERIAL		RELAY, TRIP	
TYPE & TEMPER		HEAT TREAT. SPEC.	DATE
FINISH & SPEC. NO.		ELEC. DES. APP.	MECH. DES. APP.
		10/12/59	<i>[Signature]</i> <i>[Signature]</i>
		66	AR-115 B