



CA-769

REVISIONS					
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD APPD
A	REDRAWN & REVISED				
0	ORIGINAL RELEASE FOR PRODUCTION	4-24-64		SRG	

12	LA-101-37 THRU 44	WIRE MARKERS	
11	BS-100	SOLDER, SOFT	
10	CD-101-1-MW	CORD LACING	BLACK
8	9	TE-120-2	LUG, SPADE
8	MWC 20(7) B 5	CABLE, INSULATED, FIBERGLASS	GREEN
7	95		WH/GRN
6	4		YELLOW
5	93		WH/ORN
4	92		WH/RED
3	6		BLUE
2	1		BROWN
1	MWC 20(7) B 91	CABLE, INSULATED, FIBERGLASS	WH/BRN

THIS SYMBOL DENOTES END OF INSULATION & NAIL DRIVING POINT. WIRE MUST BE STRIPPED 3/4" BEYOND THIS POINT & TINNED 1/2" UNLESS OTHERWISE SPECIFIED.

~SYMBOL NOTES~

- DENOTES ITEM NOS.
- DENOTES LUGS
- DENOTES TAGS

WIRES SHOULD BE PLACED IN CABLE IN NUMERICAL SEQUENCE AS THEY APPEAR IN ITEM COLUMN. SPACE LACING APPROX. 3/4" APART.

NOTES

1	GPT-200K	AR-156
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE	CODE	
	A	

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

F. BUDETTI

LIST OF MATERIAL

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

TITLE: CABLE ASS'Y, 40K INTERLOCK RELAY JUMPER (RELAY B)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	DRAWN W.A. FRANCO	DATE 4-24-63	FINAL APPROVAL <i>RAC</i>	DATE
	CHECKED <i>aa</i>	DATE		
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005	TOLERANCES	FRACTIONS ± 1/64 ANGLES ± 0° 30'	ELECT. DES. <i>W.B.</i>	DATE 2/13/64
			MECH. DES. <i>S.D.</i>	DATE 2-7-64

CA-769

SHEET

REV. LTR. 0