


0
CA-772

REVISIONS

SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD	APPD
A	REDRAWN & REVISED					
0	ORIGINAL RELEASE FOR PRODUCTION	4-24-64		SRG		

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
	10	LA-101-9 THRU 14	WIRE MARKERS	
	9	BS-100	SOLDER, SOFT	
	8	CD-101-1-MW	CORD, LACING	BLACK
6	7	TE-120-2	LUG, SPADE	
	6	MWC20(7)B7	CABLE, INSULATED, FIBERGLASS	VIOLET
	5		96	WH/BLUE
	4		6	BLUE
	3		91	WH/BRN
	2		8	GRAY
	1	MWC20(7)B97	CABLE, INSULATED, FIBERGLASS	WH/VIO.


THIS SYMBOL DENOTES END OF INSULATION ————
 & NAIL DRIVING POINT. WIRE MUST BE STRIPPED 3/4" BEYOND THIS POINT & TINNED 1/2" UNLESS OTHERWISE SPECIFIED.



~SYMBOL NOTES~

- DENOTES ITEM NO'S.
- ⬡ DENOTES LUGS
- DENOTES TAGS.

WIRE MUST BE PLACED IN CABLE IN NUMERICAL SEQUENCE AS THEY APPEAR IN ITEM COLUMN. SPACE LACING APPROX. 3/4" APART.



NOTES

1	GPT-200K	AR-142
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE	CODE	
	A	

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

F. BUDETTI **LIST OF MATERIAL**

MATERIAL **THE TECHNICAL MATERIEL CORP.**
MAMARONECK, NEW YORK

FINISH **TITLE**
CABLE ASSY., CROWBAR RELAY JUMPER (RELAY A)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	DRAWN: <i>G. Lincoln</i>	DATE: 4-25-63	FINAL APPROVAL: <i>[Signature]</i>	DATE:
	CHECKED: <i>W.F.</i>	DATE: 2-7-64		
DECIMALS: .X ± .05 .XX ± .01 .XXX ± .005	TOLERANCES	FRACTIONS: ± 1/64 ANGLES: ± 0° 30'	ELECT. DES: <i>[Signature]</i>	DATE: 2-7-64
			MECH. DES: <i>[Signature]</i>	DATE: 2-7-64

CA-772 0

SHEET REV. LTR.