



CA-776

REVISIONS					
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD APPD
A	REDRAWN & REVISED				
0	ORIGINAL RELEASE FOR PRODUCTION	4-24-64		SRG	

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
	10	LA-101-47 THRU 52	WIRE MARKERS	
	9	BS-100	SOLDER, SOFT	
	8	CD-101-1-MW	CORD, LACING	BLACK
6	7	TE-120-2	LUG, SPADE	
	6	MWC20(7)B5	CABLE, INSULATED, FIBERGLASS	GREEN
	5	↑ 93		WH/ORN
	4	↓ 3		ORANGE
	3	MWC 20(7) B 96		WH/BLUE
	2	MWC 18(16) B 2		RED
	1	MWC 18(16) B6	CABLE, INSULATED, FIBERGLASS	BLUE

THIS SYMBOL DENOTES END OF INSULATION → THIS EQUALS THIS

NAIL DRIVING POINT. WIRE MUST BE STRIPPED 3/4" BEYOND THIS POINT & TINNED 1/2" UNLESS OTHERWISE SPECIFIED.

WIRES SHOULD BE PLACED IN CABLE IN NUMERICAL SEQUENCE AS THEY APPEAR IN ITEM COLUMN. SPACE LACING APPROX. 3/4" APART.

NOTES

SYMBOL NOTES

- DENOTES ITEM NOS.
- ⬡ DENOTES LUGS
- DENOTES TAGS

1	GPT-200K	AR-144
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE	CODE	
	A	
THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.		

F. BUDETTI				LIST OF MATERIAL	
MATERIAL		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK			
FINISH		TITLE CABLE ASS'Y., BIAS RELAY JUMPER (RELAY A)			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		DRAWN G. Jensen	DATE 4-25-63	FINAL APPROVAL RAC	
		CHECKED W.F.	DATE 2-7-64		
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005		ELECT. DES. D.B.B.		DATE 2/12/64	CA-776
FRACTIONS ± 1/64 ANGLES ± 0° 30'		MECH. DES. D.D.		DATE 2-7-64	0
TOLERANCES				SHEET	REV. LTR.