


THIS SYMBOL DENOTES END OF INSULATION AND NAIL DRIVING POINT. WIRE MUST BE STRIPPED 3/4" BEYOND THIS POINT AND TINNED 1/2" UNLESS OTHERWISE SPECIFIED.

UNLESS OTHERWISE SPECIFIED WIRES SHOULD BE PLACED IN CABLE IN NUMERICAL SEQUENCE AS THEY APPEAR IN ITEM COLUMN BY CATEGORY.

- ALL R.F. CABLES
- ALL SHIELDED CABLES
- ALL OTHERS

SPACE LACING APPROXIMATELY 3/4" APART.



NOTES

1	GPT-10KLF	
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE 1:1	CODE A	
THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.		

CA1010 A

REVISIONS					
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD APPD
Ø	ORIGINAL RELEASE FOR PRODUCTION	2-16-66	-M	JC	
A	INCREASED LENGTH 1T. 6, 2"	6/15/66	16405	JL	QCB

SYMBOL - DENOTES

- = ITEM No's
- = LUGS
- = WIRE MARKERS

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
X	12	BS100	SOLDER, TIN ALLOY	
X	11	CD101-1-MW	CORD, NYLON, LACING	BLACK
8	10	LA101	BAND, MARKER, CBL	
8	9	TE120-2	TERM, LUG, SPADE	
	8	HWC16(19)U2	WIRE, ELECT, INS.	RED
	7	MWC18(16)U5		GREEN
	6	HWC16(19)U9		WHITE
	5	HWC18(16)U92		WH/RED
	4	MWC20(20)U2		RED
	3	MWC18(16)U9		WHITE
	2	MWC18(16)U97		VIOLET
	1	HWC18(16)U5	WIRE, ELECT, INS.	BLUE

F. BUDETTI LIST OF MATERIAL

MATERIAL _____

FINISH _____

TITLE: CABLE, ASSEMBLY (AR-173) TUNE-OPERATE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

DECIMALS: .X ± .05, .XX ± .01, .XXX ± .005

FRACTIONS: ± 1/64, ANGLES: ± 0° 30'

TOLERANCES

DRAWN: [Signature] DATE: 12-1-65

CHECKED: [Signature] DATE: 2-15-66

ELECT. DES.: [Signature] DATE:

MECH. DES.: [Signature] DATE:

FINAL APPROVAL: [Signature] DATE: 2/14/66

CA1010 A

SHEET _____ REV. LTR. _____