REVISIONS					
ZONE	SYM	DESCRIPTION	DATE	E.N.G. NO.	DRAFT	CHKD	APPD
	A	UPDATED SEE SHEETS 1 & 2	1-14-64	15933	MLA	JC	
	B	SEE SHEETS 1 & 2	2-8-64	15945	MLA	JC	
	C	TCOM R4105V DEL. FROM E101, CONN. SUPPLY, GRID TO CATHODE	5-29-64	16003	MLA	JC	
		SEE SHEET 1					
	D	R172 WAS 220 SEE SHEETS 1&2	10-9-64	16088	JL		

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
LONGLIFE			LIST OF MATERIAL	
MATERIAL			THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
FINISH			TITLE DIAGRAM, SCHEMATIC (GPR92A)	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES			DRAWN [illegible] DATE 11-6-64	FINAL APPROVED [illegible] DATE 11/16/64
TOLERANCES FRACTIONS ± 1/64 DECIMALS .X ± .03 .XX ± .010 .XXX ± .005 ANGLES ± 30'			CHECKED [illegible] DATE	SIZE CK1090 REV. D
			ENGR. APPR. [illegible] DATE	SHEET 3 OF 3

NOTES:
1 – TO SHUT OFF LOUDSPEAKER WHEN PHONES ARE INSERTED, CONNECT SPEAKER BETWEEN DESIRED TAP AND O.A. TERMINALS. FOR CONTINUOUS SPEAKER OPERATION WITH PHONES, CONNECT TO DESIRED TAP AND TERMINAL 8 GND.
2 – RESISTANCE VALUES IN OHMS, CAPACITY VALUES IN MICROFARADS AND INDUCTANCE IN MICROHENRIES UNLESS OTHERWISE SPECIFIED.
3 – ⊖ DENOTES INSULATED SWITCH TERMINALS.

NOTE:
FOR 230V OPERATION REMOVE JUMPER ~~X-X~~ AND ADD JUMPER BETWEEN TERMINAL 2 AND SELECTED TERMINAL 3.

NOTE:
"S101" IS GANGED TO RF GAIN CONTROL R110 (SEE SHEET 1).

CONTINUED FROM SHEET 2

CK-1090 D

45