

CV 10001

ISSUE	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENB. APP.	REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL						
Ø	REL. TO PRND	AUG 20/67		RPL												
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:50%;">CAPACITANCE RANGE PF</td> <td style="width:50%;">3.5/13</td> </tr> <tr> <td>CAPACITANCE TOLERANCES &amp; min max</td> <td>+10%+50%</td> </tr> <tr> <td>PERMISSIBLE TEMPERATURE RANGE</td> <td>-40 ..... +85°C</td> </tr> </table>											CAPACITANCE RANGE PF	3.5/13	CAPACITANCE TOLERANCES & min max	+10%+50%	PERMISSIBLE TEMPERATURE RANGE	-40 ..... +85°C
CAPACITANCE RANGE PF	3.5/13															
CAPACITANCE TOLERANCES & min max	+10%+50%															
PERMISSIBLE TEMPERATURE RANGE	-40 ..... +85°C															
<p>TYPE 7S TRIKO 023.5/13 pF MANUFACTURE - S10045-60</p>																
<p><b>TMC (Canada) LIMITED</b> OTTAWA ONTARIO</p>																
<p><b>CAPACITOR VARIABLE</b> CERAMIC</p>																
<p>AP DRAWN RPL ELEC. DES. APP. [Signature] CHECKED [Signature] FINAL APPROVAL [Signature]</p>																
<p>CV 10001 Ø</p>																