IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES





SECTION "A-A"

SPOTWELD REINFORCING STRIPS OF #12 GUAGE STEEL FOR TAPPING THICKNESS - 2 REQ.

NOTICE TO PERSONS RECEIVING THIS DRAWING

THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

Property of:
THE TECHNICAL MATERIEL CORPORATION
MAMARONECK, NEW YORK

LEGEND FOR HOLES & TAPS

A - DRILL & TAP FOR 10-32 CL-2	4 REQ.
B - 13/64 (.203) DIA.	4 REQ.
C - .136 DIA.	6 REQ.
D - 1" DIA.	16 REQ.

MATERIALS:
STEEL, MILD COLD ROLLED 16 GA. (.059)
METAL TO BE FREE OF ALL SURFACE IMPERFECTIONS

FINISHES:
F-371 DEGREASING FOR STEEL
F-114 ZINC CHROMATE PRIMER
F-220 RCAF SMOOTH BLUE ENAMEL

MANUFACTURING PROCESS:
FRONT OPENINGS SHOULD BE WITHIN ± 1/64
SQUARE OF CABINET SHOULD BE WITHIN 0.5°
AS MANY SPOTWELDS AS PRACTICABLE FOR MAXIMUM STRENGTH & DEPENDABILITY.

ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.

TOLERANCES AS NOTED SCALE: 6"=1'0"

ALL OTHERS: DEC. DIM. ± / FRAC. DIM. ± 1/64 See Note / ANGULAR DIM. ± — DRILL PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS TOLERANCES ARE NOT INCLUDED.

FORM—111

REQ PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
1	MSR-4		A-1555	6-19-58
1	MSR-3		A-1555	6-19-58
1	MSR-1		A-1555	6-19-58

USED ON

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
SEE NOTES			THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK	
STOCK SIZE				
SEE NOTES		C/O	CABINET, ELECTRICAL	
MATERIAL		WEIGHT PER PC.	MODEL - MSR	
SEE NOTES			6/19/58	
TYPE & TEMPER			DRAWN	ELEC. DES. APP. / MECH. DES. APP.
HEAT TREAT. SPEC.			CHECKED	FINAL APPROVAL
SEE NOTES				MS-1287
FINISH & SPEC. NO.				