



A - $\frac{11}{64}$ DIA. 4 REQ.
 B - .191-.194 DIA. 4 REQ.

NOTE:
 USE MATERIAL THICKNESS FOR MAX. RADIUS ON ALL BENDS UNLESS OTHERWISE SPECIFIED.

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES AND INCLUDE
 CHEMICALLY APPLIED OR PLATED FINISHES

DECIMALS .X ± .05 FRACTIONS ± 1/64
 .XX ± .01 ANGLES ± 0° 30'
 .XXX ± .005 TOLERANCES

SEE HERE FOR QUANTITY FEED 2-246

4	1	NT-129-632-4	NUT, ROUND, SWAGE TYPE
REQ. ITEM	PART NO.		DESCRIPTION
	.064		THE TECHNICAL MATERIEL CORP.
	STOCK SIZE		MAMARONECK, NEW YORK
	ALUMINUM		SUPPORT, SUB-CHASSIS
	MATERIAL		
	5052-H32		
	TYPE & TEMPER	HEAT TREAT. SPEC.	
	3404 YELL. IRIDITE		
	FINISH & SPEC. NO.		
	ELEC. DES. APP.	MECH. DES. APP.	SHEET OF
			MS-2490

SYM	ZONE	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES			SCALE				
TOLERANCES ON FRACTIONS ± 1/64			MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS & SHARP EDGES				
DECIMALS ± .005			ANGLES ± 1/2°				