



MATERIAL:
 .051 PERFORATED ALUM. 5052 H32
 .072 DIA. HOLES ON 1/8 CENTERS
 STAGGERED.

UNLESS OTHERWISE SPECIFIED:
 1. USE MATERIAL THICKNESS FOR MAX. RADIUS ON ALL BENDS UNLESS OTHERWISE SPECIFIED
 2. REMOVE ALL BURRS AND SHARP EDGES

| | | | | | | | |
|-----------------------------|------|----------------|--|---------|--------|---------|-----------|
| SYM | ZONE | DESCRIPTION | DATE | CH. NO. | DRAFTS | CHECKER | ENG. APP. |
| A | - | MAT'L WAS .064 | 1/9/64 | 10742 | | | |
| UNLESS OTHERWISE SPECIFIED: | | | SCALE 1:2 | | | | |
| DIMENSIONS ARE IN INCHES | | | MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS & SHARP EDGES | | | | |
| TOLERANCES ON | | | | | | | |
| FRACTIONS ± 1/64 | | | DECIMALS ± .005 | | | | |
| | | | ANGLES ± 1/2° | | | | |

| | | | | |
|---------------|-------|---------|------------|--------|
| REQ. PER UNIT | MODEL | SECTION | ASS'Y. NO. | DATE |
| 1 | LFA-4 | | | 5-2-63 |
| USED ON | | | | |

| | | | | | |
|---------------------|------|----------|------------------------------|-------------|---------|
| 5 | 2 | FS-109-3 | RING, STUD RETAINING | | |
| 5 | 1 | FS-110-1 | STUD SLOTTED HEAD | | |
| REQ. | ITEM | PART NO. | POSE | DESCRIPTION | SYMBOL |
| .064 | | | THE TECHNICAL MATERIEL CORP. | | |
| SEE NOTE | | | MAMARONECK, NEW YORK | | |
| MATERIAL | | | COVER, BOTTOM | | |
| 5052 H32 H32 | | | 5-2-63 | TF-4 | 6-11-63 |
| TYPE & TEMPER | | | DRAWN | | |
| HEAT TREAT. SPEC. | | | CHECKED | | |
| S404-YELLOW IRIDITE | | | FINAL APPROVAL | | |
| FINISH & SPEC. NO. | | | MS-3365 A | | |
| ELEC. DES. APP. | | | MECH. DES. APP. | | |
| SHEET | | | OF | | |