REVISIONS							
ZONE	SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD	APPD
#	X	EXPERIMENTAL RELEASE	4-17-64		G.D.L		
	X2	SPOTFACE ADDED	7-10-64	#	N.P.	@	
#	Ø	ORIGINAL RELEASE FOR PRODUCTION	8.11.64	#	NB		

HOLE	DESCRIPTION	REQ
A	.125 DIA	18
B	.144 DIA	8
C	.191 - .194 DIA.	4
D	.167 DIA THRU & C'SINK 90° X .179 DIA.	8
E	.189 DIA.	3
F	.296 DIA	2
G	.250 DIA	1
H	SPOTFACE 7/16 DIA (SEE NOTE 1)	3
J	SPOTFACE 3/4 DIA (SEE NOTE 1)	1



METAL STAMP TMC PART NO. 1/8 HIGH GOTHIC.
WITH LATEST REVISION LETTER



NOTE:
1. AFTER FINISH SPOTFACE TO REMOVE FINISH WHERE INDICATED.

UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS.
2. ALL ANGULAR BENDS 90°.
3. REMOVE ALL BURRS AND SHARP EDGES.
4. MOUNT INSERTS AFTER FINISHING.

NOTES

MS 3745 Ø

REF: LD1488

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
4	1	NT-129-632-4	NUT, ROUND, SWAGE TYPE	C

ANGER — LIST OF MATERIAL

Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
1	HFR-2	A3648

MATERIAL: .081 THK ALUMINUM 5052-H32

FINISH: BLACK ANODIZED

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

TITLE: CHASSIS, POWER SUPPLY

SCALE 1:1 | CODE A

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES: DECIMALS .X ± .05, .XX ± .01, .XXX ± .005; FRACTIONS ± 1/64; ANGLES ± 0° 30'

		DATE
DRAWN	G.D.L	4-16-64
CHECKED	@	8-11-64
ELECT. DES.	Stanger	7/29/64
MECH. DES.		

FINAL APPROVAL: [signature] DATE

MS 3745 Ø

SHEET — REV. LTR.

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

TMC FORM 110

REPROVEL NO. 440H 16100