



REQ. PER UNIT	USED ON		
	MODEL	ASS'Y. NO.	DATE
5	PFCB-1		9-18-64

MS4038 B

HOLE	DESCRIPTION	REQ.
A	.161-.164 DIA	4

UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS .
2. ALL ANGULAR BENDS 90 DEGREES
3. REMOVE ALL BURRS AND SHARP EDGES
4. MOUNT INSERTS AFTER FINISHING

OPPOSITE SIDE IDENTICAL

1 MOUNT IN ALL "A" HOLES

MS4038-

METAL STAMP TMC PART NO. 1/8 HIGH, WITH LATEST REVISION LETTER.

SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
B	U/O! QTY/UNIT WAS 7.	1-12-65	13256	9L		
A	45° CUTOUT ADDED.	10-9-64	12604	bstb		
Ø	ORIGINAL RELEASE FOR PRODUCTION	9-25-64	Ø.	9L		
X	EXPER. RELEASE	9-18-64	X			

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

SCALE 1:1

DECIMALS .X ± .05 .XX ± .01 .XXX ± .005

FRACTIONS ± 1/64 ANGLES ± 0° 30'

TOLERANCES A

4	1	NT129-440-3	NUT, PLAIN SPLINE TYPE	A
REQ. ITEM	PART NO.		GELMAN DESCRIPTION	SYMBOL
	.051		THE TECHNICAL MATERIEL CORP.	
	STOCK SIZE		MAMARONECK, NEW YORK	
	ALUMINUM		PLATED SHIELD	
	MATERIAL		PRINTED CIRCUIT	
5052-H32			Q. Law J.R.S@	
TYPE & TEMPER	HEAT TREAT. SPEC.	DRAWN	CHECKED	FINAL APPROVAL
5404 YELLOW IRIDITE				
FINISH & SPEC. NO.	ELEC. DES. APP.	MECH. DES. APP.	MS4038 B	