



REVISIONS						
REV	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD	APPD
X	EXPER. RELEASE					
X1	TWO "B" HOLES DELETED	12-9-64		G.D.L		
0	ORIGINAL RELEASE FOR PRODUCTION	4-9-65	0	2L		

HOLE	DESCRIPTION	REQ.
A	9/64 DIA.	8
B	5/32 DIA.	6

UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
2. ALL ANGULAR BENDS 90 DEGREES
3. REMOVE ALL BURRS AND SHARP EDGES
4. MOUNT INSERTS AFTER FINISHING

* CUTOUTS CENTERED BETWEEN HOLES

REF: LD 1667

REQ'D.	PART NUMBER	DESCRIPTION	SYMBOL
	0. POSE	LIST OF MATERIAL	
MATERIAL		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
.093 THK ALUMINUM 5052-H32		CHASSIS, XFMR, BAND 3,4,5	
FINISH		TITLE	
S404 YEL IRIDITE			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		DRAWN G.D.L	DATE 12-9-64
		CHECKED @	DATE
		ELECT. DES.	DATE
		MECH. DES. H.P.Z.	DATE 4-8-65
		FINAL APPROVAL 	DATE
		MS 4063	REV. LTR. 0
		SHEET	

METAL STAMP TMC P/No. 1/8 HIGH
GOTHIC W/LATEST REV. LETTER

3	VLRB-1	
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE 1:1	CODE A	

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY
OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR
REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

DECIMALS
.X ± .05
.XX ± .01
.XXX ± .005

TOLERANCES

FRACTIONS
± 1/64
ANGLES
± 0° 30'

NOTES