


HOLES
A - .250 MIN., .253 MAX. DIA'S
FOR MTG NT-129-1032-4

REQ.
3

DRILL .120 DIA.
THRU. CSK
82° X .230 DIA
(2 REQ)



"B" DETAIL
2 REQ.

"C" HOLE
13/16 DIA.
2 REQ.

REVISIONS				
SYM	DESCRIPTION	DATE	E.M.N. NO.	APPD
Ø	ORIGINAL RELEASE FOR PRODUCTION	8/16/69	Ø	



- UNLESS OTHERWISE SPECIFIED:
1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS.
 2. ALL ANGULAR BENDS 90°.
 3. REMOVE ALL BURRS AND SHARP EDGES.
 4. MOUNT INSERTS AFTER FINISHING.

NOTES

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

3	1	NT-129 1032-4	NUT, ROUND, SWAGE TYPE	
REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
LIST OF MATERIAL				
MATERIAL		.064 THICK ALUMINUM, 5052 - H 32		
FINISH		S404-IRIDITE, 14-2 AL COAT		
TITLE		BRACKET, SHIELD, MTG		
THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK				
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	DRAWN <i>PJM</i>	DATE 4-19-65	FINAL APPROVAL <i>[Signature]</i>	DATE 8/8/69
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005	TOLERANCES	FRACTIONS ± 1/64 ANGLES ± 0° 30'	MS4517	
SCALE 1=1		CODE A	DATE 7/22/65	REV. LTR. Ø
QTY./UNIT 1		MODEL USED ON TSTE-10K	ASS'Y. NO.	SHEET