



METAL STAMP TMC PART NO. 1/8 HIGH GOTHIC.
WITH LATEST REVISION LETTER.

REVISIONS							
ZONE	SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD	APPD
	X1	NT WAS B32, EDIMENSINHPD "C" HOLES	26 JAN 66				
	Ø	ORIGINAL RELEASE FOR PRODUCTION	3/2/66				

- A ~ .191-.194 DIA. 10 REQ.
- B ~ 13/64 DIA. 4 REQ.
- C ~ 3/32 DIA. 3 REQ.
- D ~ 1 5/8 DIA. 1 REQ.

SADVEL IRIDITE
S114 ZINC CHROMATE PRIMER } OUTSIDE & EDGES
S520 ECAF BLUE ARMORHIDE } ONLY.

- UNLESS OTHERWISE SPECIFIED:
1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
 2. ALL ANGULAR BENDS 90 DEGREES
 3. REMOVE ALL BURRS AND SHARP EDGES
 4. MOUNT INSERTS AFTER FINISHING

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
10	1	NT129-632-4	NUT, PLN, SPLINE	A

LIST OF MATERIAL

MATERIAL	064 ALUM. 5052 H32	THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK
FINISH	SEE NOTES	TITLE BRACKET, HOSE MOUNTING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	DRAWN RJM	DATE 3 DEC 65	FINAL APPROVAL M. H. HAY	DATE 3/2/66
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005	FRACTIONS ± 1/64 ANGLES ± 0° 30'	ELECT. DES. RSP	MECH. DES. RSP	DATE 2/2/65

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

NOTES

MS4854