


| TMC PART NO. | MFR'S No. | IMPEDANCE |
|--------------|-----------|-----------|
| PO 277-1 | 75AR | 50 Ω |
| PO 277-2 | 75AR-75 | 75 Ω |

| REQ. PER UNIT | USED ON | | PO 277 | Ø |
|---------------|---------|------------|---------|---|
| | MODEL | ASS'Y. NO. | | |
| | | | 7-28-75 | |



| ISSUE | ITEM | CHANGED FROM | DATE | CH. NO. | DRAFTS | CHECKER | ENG. APP. | REQ. ITEM | PART NO. | DESCRIPTION | SYMBOL | | |
|---|------|------------------|--------|---------|--------|---------|-----------|---|-------------------|--|---------|----------------|--|
| Ø | | ORIGINAL RELEASE | 9/2/75 | | cl. | | | | | TMC INDUSTRIAL CORP. MAMARONECK. NEW YORK | | | |
| | | | | | | | | | | 7/8 EIA FLANGE | | | |
| TOLERANCES | | | | | | | | SCALE: 401-31 | | | | | |
| DEC. DIM. ± FRAC. DIM. ± ANGULAR DIM. ± | | | | | | | | MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES | | | | | |
| | | | | | | | | TYPE & TEMPER | HEAT TREAT. SPEC. | DRAWN | CHECKED | FINAL APPROVAL | |
| | | | | | | | | FINISH & SPEC. NO. | ELEC. DES. APP. | MECH. DES. APP. | | | |
| | | | | | | | | | | | | PO 277- Ø | |