



SW 417-A

REVISIONS						
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD	APPD
X1	VOLTAGE RATING WAS 250V 60 CPS AC	4-30-66	X1	G.D.L.		
0	ORIGINAL RELEASE FOR PRODUCTION	5-18-66	0	UW		HG
A	ADDED TWO AUX. SWITCHES	8-2-66	16603	RME		gc

TMC PART NO.	MFG. PART NO.	CURRENT RATING AMPS	CURVE
SW 417-1	AM333HHHE MG6-25	25	4

— SPECIFICATIONS —
 NO. OF POLES : 3W / 3PDT AUXILIARY
 VOLTAGE RATING : 250V 50/60 CPS AC
 TRIP : COMMON
 CASE : PLASTIC, FUNGUS & MOISTURE TREATED

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
--------	------	-------------	-------------	--------

LIST OF MATERIAL				
MATERIAL		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK		
FINISH		TITLE CIRCUIT BREAKER 3 POLE W/AUX.		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		DRAWN G.D.L.	DATE 12-8-65	FINAL APPROVAL [Signature]
		CHECKED [Signature]	DATE 12-14-65	DATE 5/18/66
		ELECT. DES. [Signature]	DATE 12/15/65	DATE 5/18/66
		MECH. DES. [Signature]	DATE 5/18/66	DATE 5/18/66

1	TST () 2.5K	TCP-2
QTY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE DO NOT SCALE	CODE C	S401-58

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

DECIMALS	TOLERANCES	FRACTIONS
X ± .05		± 1/64
XX ± .01		ANGLES ± 0° 30'
XXX ± .005		